Integrating spatial-logical constraints in the loss function for medical segmentation

Francesco Girardello
University of Pisa

Summary

- Introduction
- Problem formulation
- Hybrid system
- Neuro-symbolic Loss
- Preliminary Results
- Conclusion & Future Directions


Introduction - Medical segmentation

What is medical segmentation?

Why is it important?

Problems of manual segmentation:

- Time-consuming
- Inter-annotator variability
- Human error
- Scalability
- Specialist dependency



Automatic Medical segmentation



LOGICAL APPROACH (e.g., VoxLogicA)

- Explainability (White-box)
- No Training Data Needed
- Verifiable Rules & Guidelines
- Computationally Efficient


DEEP LEARNING APPROACH (e.g., nnU-Net)

- High Accuracy & Performance
- Automated Feature Learning
- State-of-the-Art Results
- Handles Complex Patterns

Spatial Model Checking

Spatial Model Checking for Images

Applies formal methods to image analysis and uses logical formulas to identify pixels with specific spatial properties



Advantages


✓ **Complete Transparency**
Every step is traceable

✓ **Formal Verification**
Mathematical guarantees

✓ **Clinical Alignment**
Encodes expert knowledge

VoxLogicA: Spatial Model Checking

VoxLogicA



Intensity-based operators: Define regions based on image intensity values (<., >., =.)

Example: let whiteDots = (intensity =. 255) identifies pixels with intensity value 255

Distance operators: Express metric relationships between spatial regions (pdt)

Example: pdt(redDot) <=. threshold identifies all points within a specified distance from a reference region

Topological operators: Express connectivity and reachability properties (~> N)

Example: corridors ~> N(entrance) finds all corridor pixels reachable from the entrance

Boolean operators: Combine spatial predicates (& (AND), | (OR), ! (NOT))


Example: let common = reachableFromEntrance & reachableFromExit computes intersection


From CNN to NNu-Net

Convolutional Neural Networks:

CNNs are a specific type of neural network optimized for image recognition. They rely on three fundamental ideas:

- **Convolution**
- **Pooling:**
- **Feature Hierarchy**






U-Net architecture and nnU-Net Framework

U-Net Architecture

- Skip connections
- Multi-scale features
- Spatial preservation

nnU-Net Framework

- Automatic preprocessing
- Dynamic adaptation
- Hyperparameter optimization



nnU-Net: a self-configuring method for deep learning-based biomedical image segmentation

Fabian Isensee, Paul F. Jaeger, Simon A. A. Kohl, Jens Petersen & Klaus H. Maier-Hein

Nature Methods **18**, 203–211 (2021) | Cite this article

nnU-Net loss function - Dice score

How does nnU-Net improve its weights to obtain correct segmentations?


$$\mathcal{L}_{\text{NnuNet}} = \mathcal{L}_{Dice} + \mathcal{L}_{CE}$$

$$p_i \in [0,1] \quad , \quad g_i \in \{0,1\}$$

$$\mathcal{L}_{\text{Dice}} = 1 - \frac{2\sum_i p_i g_i + \epsilon}{\sum_i p_i + \sum_i g_i + \epsilon}$$

Dice Coefficient

$$\text{Dice} = \frac{2|P \cap G|}{|P| + |G|}$$





$$\mathcal{L}_{\text{CE}} = -\sum_i [g_i \log(p_i) + (1 - g_i) \log(1 - p_i)]$$

The problem with deep learning

Medical segmentation with NN-uNet

- **Accountability:** ensuring compliance with clinical guidelines
- **Tunability:** allowing practitioners to adjust parameters for specific protocols.
- **Explainability:** providing clear and understandable explanations.






Geometric and Topological Understanding

Recent studies have shown that nnU-Net struggles to recognize specific geometric and topological properties, including:

- Distance-based tasks for geometric comprehension (top)
- Connectivity analysis for topological understanding (bottom)



A Multi-Resolution Benchmark Framework for Spatial Reasoning Assessment in Neural Networks

Manuela Imbriani,[1,2,a)] Gina Belmonte,[3] Mieke Massink,[2] Alessandro Tofani,[3] and Vincenzo Ciancia[2]

[1]*Dipartimento di Fisica, Università di Pisa, Pisa, ITALY*
[2]*Istituto di Scienza e Tecnologie dell'Informazione "A.Faedo", CNR, Pisa, ITALY*
[3]*Azienda Toscana Nord Ovest, S.C.Fisica Sanitaria Nord, Lucca, ITALY*

The hybrid advantage: logic and deep learning




High Accuracy Maintained. Achieves state-of-the-art performanc

Explainable & Transparent. Final segmentation is backed by explicit, clinically-valid logical rules.

Enforced Anatomical Consistency. Corrects topological errors for biologically plausible results.

Flexible & Adaptable. Rules can be adjusted for new protocols without retraining the network.

The mechanism of hybridization




Results of this methods

Contents lists available at ScienceDirect

Artificial Intelligence In Medicine

journal homepage: www.elsevier.com/locate/artmed



Research paper

Symbolic and hybrid AI for brain tissue segmentation using spatial model checking☆

Gina Belmonte [a], Vincenzo Ciancia [b], Mieke Massink [b,*]

[a] S. C. Fisica Sanitaria Nord, Azienda Toscana Nord Ovest, Lucca, Italy
[b] Istituto di Scienza e Tecnologie dell'Informazione 'A. Faedo', Consiglio Nazionale delle Ricerche, Pisa, Italy

Table 6

GTV-optimal using tabulation to get optimal thresholds w.r.t. BraTS 2020 ground truth; GTV-nnAsGT using nn-Unet result as ground truth for finding optimal thresholds; GTV-nnU segmentation result from ML algorithm trained with 50 cases; GTV-symbolic segmentation with pure symbolic specification of Section 4.

	Dice (234 cases)			Sensitivity (234 cases)			Specificity (234 cases)		
	Mean (Stdev)	Range	Median (IQR)	Mean (Stdev)	Range	Median (IQR)	Mean (Stdev)	Range	Median (IQR)
GTV-optimal	0.884* (0.075)	0.58–0.97	0.913 (0.07)	0.87* (0.10)	0.43–0.98	0.91 (0.09)	1.00* (0.00)	0.99–1.00	1.00 (0.00)
GTV-nnAsGT	0.867* (0.087)	0.46–0.97	0.895 (0.10)	0.85* (0.122)	0.42–1.00	0.89 (0.13)	1.00* (0.001)	0.99–1.00	1.00 (0.00)
GTV-nnU	0.891* (0.082)	0.42–0.98	0.914 (0.07)	0.92* (0.841)	0.27–1.00	0.94 (0.08)	0.99* (0.00)	0.99–1.00	1.00 (0.00)
GTV-symbolic	0.848 (0.11)	0.0–0.97	0.884 (0.103)	0.88 (0.126)	0.00–1.00	0.92 (0.13)	1.00 (0.00)	0.98–1.00	1.00 (0.00)

* Denotes Wilcoxon signed-rank statistical test with p-value < 0.01 with respect to the GTV-symbolic segmentation with a fixed pair of pre-established thresholds (vI = 88, hI = 93) used for all cases.

Synergistic integration proposed

VoxLogicA:

Extract Geometrical Constraint

Input Data


(Dataset of Medical Image)

nnU-Net Prediction:

nnU-Net Adjust with the constraint in the loss

Final Output:

Geometrically consistent segmentation output



Improvements:

- **Synergistic:** Single unified model, no post-processing.
- **Superior Performance:** Outperforms baseline nnU-Net.
- **Tunable:** Geometric terms independently weighted.
- **Geometry-Aware:** Constraints learned during training.

The differentiable neuro-symbolic loss

1. The Hybrid Loss Equation
(Integrating Logic)


$$\mathcal{L}_{Total} = \underbrace{\mathcal{L}_{DiceCE}}_{\text{Data Fidelity}} + \lambda \sum_{k} w_k \cdot \underbrace{\mathcal{L}_{Logic}^{(k)}}_{\text{Spatial Constraints}}$$

- Standard accuracy term (e.g., overlap)
- Regularization weight (Curriculum Learning)
- Differentiable translation of logical rules

Goal: Force the network to learn latent representations that intrinsically respect anatomical rules.


2. The Innovation: Making Logic Differentiable
(Fuzzy Relaxation)

The Problem: Discrete Logic Breaks Backprop



Null Gradients -> No Learning

The Solution: Fuzzy Logic Relaxation



Continuous Gradients -> Enable Backpropagation

Differentiable Operators:
- **Soft Area/Perimeter** (Probabilistic sums, Sobel kernels)
- **Inertia Tensors** (Eigenvalue analysis for shape)


Key Advantages:
- ☑ **Training Stability** (vs. GANs)
- ☑ **Explainability** (Known penalty reasons)

Synthetic validation

Dataset consisting of 500 grayscale images (512×512 pixels) containing:

1. One target circle (radius 25-55px) with intensity gradient
2. Distractor shapes (polygons: triangles, squares, pentagons, hexagons)
3. Partial occlusions (2-5 black rectangles covering parts of the image)
4. Gaussian noise (σ=10)

Objective: segment the circle despite occlusions and distractors.



Input image | Ground truth

Spatial reasoning timeline - Soft logic

1. Decoder Output (Logits)
Generates raw scores for classes per pixel

2. Softmax Function
Converts raw scores into probability values (0-1). Total sum = 1


3. Probability Slicing
Isolates the specific probability map of the Tumor class

4. Fuzzy Geometric Operations
Computes "soft" Area and Perimeter using sums and gradients

5. Logical Loss Calculation
Measures deviation from logical rules (e.g., shape constraint)

6. Backpropagation
Updates network weights to minimize the loss.

Discrete World (Hard Logic)




Binary Mask

$$C = \frac{4\pi \cdot \text{Area}}{\text{Perimeter}^2}$$

Hard Area:
Count(pixels)
$\sum_i M_i$

Hard Perimeter:
Count(boundary pixels)

Differentiable World (Soft Logic)



Probability Map

$$\mathcal{L}_{\text{Compact}} = \left| \frac{4\pi \cdot \text{A}_{\text{soft}}}{(\text{P}_{\text{soft}})^2} - 1 \right|$$

Soft Area:
Sum of Probabilities
$\text{A}_{\text{soft}} = \sum_i P(x_i)$

Soft Perimeter:
Sum of Gradient Magnitude
$P_{\text{soft}} = \sum_i \|\nabla P(x_i)\|$

Spatial constraints in the loss - Compactness

$$\mathcal{L}_{\text{Logic}} = w_c \mathcal{L}_{\text{comp}} + w_b \mathcal{L}_{\text{boundary}} + w_e \mathcal{L}_{\text{circle}}$$

$$\mathcal{L}_{\text{comp}} = 1 - \frac{4\pi A}{P^2}, \qquad A = \sum_{i,j} p_{ij}$$

$$P = \sum_{i,j} \sqrt{\left(\frac{\partial p}{\partial x}\Big|_{ij}\right)^2 + \left(\frac{\partial p}{\partial y}\Big|_{ij}\right)^2}$$

1. Compactness Loss (Isoperimetric Index)



Penalizes Deviation from Roundness




$$C = \frac{4\pi \cdot \text{Area}}{\text{Perimeter}^2}$$

Spatial constraints in the loss - Boundary


$$\mathcal{L}_{\text{Logic}} = w_c \mathcal{L}_{\text{comp}} + w_b \mathcal{L}_{\text{boundary}} + w_e \mathcal{L}_{\text{circle}}$$

$$\mathcal{L}_{\text{boundary}} = \text{mean}\left(p_{ij} \cdot \left|\nabla^2 p_{ij}\right|\right)$$

2. Boundary Smoothness Loss



Favors Smooth Contours



Metric: Variance of Laplacian

Spatial constraints in the loss - Circle


$$\mathcal{L}_{\text{Logic}} = w_c \mathcal{L}_{\text{comp}} + w_b \mathcal{L}_{\text{boundary}} + w_e \mathcal{L}_{\text{circle}}$$

$$\mathcal{L}_{\text{circle}} = \frac{\sum_{i,j} (p_{ij} - T_{ij})^2}{\sum_{i,j} T_{ij} + \varepsilon}$$

$$T_{ij} = \sigma(k \cdot (r - d_{ij})), \qquad r = \sqrt{\frac{A}{\pi}}$$

$$d_{ij} = \sqrt{(i - c_x)^2 + (j - c_y)^2}$$

3. Circle Loss



Penalizes Elongation

Ratio λ_1/λ_2

nnU-Net Evaluation: key metrics

1. OVERLAP METRICS (VOLUME)

Measure correctly identified pixels vs. total.

- **DICE**: Balances precision & recall. Standard for total mass.
- **IOU (Intersection over Union)**: Ratio of intersection to union. More strict on small errors.

2. GEOMETRY & SHAPE METRICS (APPEARANCE)

Measure if predicted shape respects properties.

- **COMPACTNESS**: Similarity to a circle. Low for elongated roads.
- **ECCENTRICITY**: Elongation. Near 1 ideal for roads.

3. BOUNDARY & DISTANCE METRICS (EDGES)


Focus on boundaries and spatial error position.

- **BOUNDARY IOU**: Overlap along contours only, ignoring internal area.
- **HAUSDORFF DISTANCE**: Max distance between prediction and reality. Finds hallucination.

Preliminary results


Top row:
results from the Baseline model (standard nnU-Net).

Bottom row:
results from the Geometric Loss model.



Preliminary results

The reported results represent the mean values of all 6 metrics computed on the test set, with baseline nnU-Net on the left and hybrid loss on the right.




Research Progress and Roadmap

PART 1 – GEOMETRIC


- [x] Find an appropriate synthetic dataset
- [x] Create differentiable spatial constraints (relative)
- [x] Show that the geometric model is better than baseline model
- [–] Verify how the improvement of the geometric model varies depending on the test set or on the training images

PART 2 – MEDICAL

- [–] Extract tumor rules with VoxLogicA
- [ ] Make these rules differentiable
- [ ] Create a differentiable loss for tumor segmentation
- [ ] Compare with the state-of-the-art nnU-Net baseline



Conclusions




Thank you for your attention and feedback
Contact: francesco.girardello@isti.cnr.it